


PIN	SYMBOL
1	VBL-
2	VBL-
3	VBL+
4	VBL+
5	Y1
6	X1
7	NC
8	RESET
9	SPENB
10	SPCK
11	SPDA
12	B0
13	B1
14	B2
15	B3
16	B4
17	B5
18	B6
19	B7
20	G0
21	G1
22	G2
23	G3
24	G4
25	G5
26	G6
27	G7
28	R0
29	R1
30	R2
31	R3
32	R4
33	R5
34	R6
35	R7
36	HSYNC
37	VSYNC
38	DOTCLK
39	NC
40	NC
41	VCC
42	VCC
43	Y2
44	X2
45	NC
46	NC
47	NC
48	IF2
49	IF1
50	IF0
51	NC
52	DEN
53	GND
54	GND

- NOTE:
- 1 DISPLAY TYPE: 3.5" TFT TRANSMISIVE
 - 2 VIEW DIRECTION: 12 O'CLOCK
 - 3 Resolution: 320(RGB)X240 DOTS
 - 4 DRIVER IC: HX8238-D
 - 5 PIXEL PITCH: 0.219 X 0.219 mm
 - 6 BackLight: 6 chip White LED (串联)
 - 7 OPERATION TEMP.: -20°C~+70°C
 - 8 STORAGE TEMP.: -30°C~+80°C
 - 9 UNSPECIFIED TOLERANCES IS ±0.3mm.
 - 10 All material comply with ROHS



SinoCrystal (ShenZhen) Tech CO., LTD.		
绘图: LiuJun	产品型号: SCT035001-V04	单位: mm
审核:	图纸编号: WXT-SCT035001-V04	日期: 2015.10.13
批准:	图纸版号: A0	页数: 1/1